

1 Port USB PS/2 Server Remote Control IP KVM Switch with Virtual Media

StarTech ID: SV1108IPEXGB



The SV1108IPEXGB 1 Port USB PS/2 Server Remote Control IP KVM Switch with Virtual Media lets you control a USB or PS/2 server remotely over a LAN or the Internet.

The 1 port KVM over IP includes all necessary KVM cables, and offers KVM control from the BIOS-level onward. Reboot, monitor the entire boot process, and interact with your connected system easily. RS232 support also lets you connect to a serial console device via Telnet or SSH.

Virtual Media lets you execute files via USB from the remote console as if they were local to the connected server. Perfect for remote driver updates, patches, application or OS installation.

The Java-based browser utility ensures the IP remote control unit is compatible with many current web browsers, and almost any operating system on the market.

Multiple integrated security features ensure a reliable single port IP KVM connection, including password-protection, IP/MAC address filtering, external authentication (RADIUS, LDAP, LDAPS, Active Directory) and advanced encryption (56-bit DES, 168-bit 3DES, 256-bit AES, 128-bit RC4).

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Remote access to a mission-critical server
- BIOS level remote access to servers at co-location, ISP and MSP locations
- Small to Medium businesses that require access to individual servers without breaching security to others

Features

- Full, BIOS-level control of a remote system over the internet
- Supports USB or PS/2 keyboard and mouse
- Supports resolutions up to 1600x1200
- Includes all necessary KVM Cables
- USB virtual media port for disk emulation and file transfers, including complete remote application and operating system installations
- Browser-based login for compatibility with most operating systems
- Java client available for Windows® systems
- Security features include: SSL Encrypted Login, IP/MAC filtering, Password Protection, Encryption (56-bit DES, 168-bit 3DES, 256-bit AES, 128-bit RC4) and External Authentication (RADIUS, LDAP, LDAPS, Active Directory)
- RS-232 console support for Telnet or SSH terminal access

Technical Specifications

| | |
|----------------------------|---|
| Warranty | 2 Years |
| Audio | No |
| Cables Included | Yes |
| Daisy-Chain | No |
| KVM Ports | 1 |
| Multi-Monitor | No |
| PC Interface | USB and PS/2 |
| PC Video Type | VGA |
| Rack-Mountable | Yes |
| Console Interface(s) | 1 - VGA (15 pin; High Density D-Sub) Male |
| Console Interface(s) | 2 - PS/2 (6 pin; Mini-DIN) Female |
| Console Interface(s) | 2 - USB A (4 pin) Female |
| Host Connectors | 1 - USB A (4 pin) Female |
| Host Connectors | 1 - VGA (15 pin; High Density D-Sub) Female |
| Host Connectors | 2 - PS/2 (6 pin; Mini-DIN) Female |
| Other Interface(s) | 1 - DB-9 (9 pin; D-Sub) Male |
| Other Interface(s) | 1 - RJ-45 Female |
| Other Interface(s) | 1 - USB Mini-B (5 pin) Female |
| DVI Support | No |
| IP Control | Yes |
| Maximum Analog Resolutions | 1600x1200 @ 60Hz |
| Security Features | 128-bit SSL Encryption |
| Security Features | 3DES |
| Security Features | AES |
| Security Features | DES |
| Security Features | IP Filtering |
| Security Features | MAC Address Filtering |
| Security Features | RC4 |
| Supported Protocols | RADIUS, LDAP, LDAPS, Active Directory |

| | |
|-------------------------------|---|
| Supported Protocols | TCP/IP, HTTP, HTTPS, UDP, DHCP, SSL, ARP, DNS, ICMP, CHAP, PPP |
| Supported Resolutions | 1600x1200, 1280x1024, 1280x720, 1152x864, 1024x768, 800x600, 720x400, 640x480 |
| OS Compatibility | OS independent; No software or drivers required |
| Color | Black |
| Enclosure Type | Steel |
| Product Height | 25 mm [1 in] |
| Product Length | 200 mm [7.9 in] |
| Product Weight | 485 g [17.1 oz] |
| Product Width | 80 mm [3.1 in] |
| LED Indicators | 1 - 10/100 Mbps (Orange/Green) |
| LED Indicators | 1 - Link |
| LED Indicators | 1 - Power |
| Center Tip Polarity | Positive |
| Input Current | 0.5 A |
| Input Voltage | 100 ~ 240 AC |
| Output Current | 2.4 A |
| Output Voltage | 5.3 DC |
| Power Adapter Included | Yes |
| Power Consumption | 6.3 W |
| Humidity | 0~80% RH (Non-Condensing) |
| Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| System and Cable Requirements | Browsers supported for remote login include: Internet Explorer, Chrome, Firefox, Safari, Opera, Mozilla and Netscape. Please refer to product manual for compatible version numbers |
| System and Cable Requirements | Connected server and remote user computers can be using any operating systems capable of running Sun Java Runtime Environment (JRE) 6, Update 3 or higher |
| Shipping (Package) Weight | 1.4 kg [3.2 lb] |
| Included in Package | 1 - IP KVM Switch |
| Included in Package | 1 - Console Cable |
| Included in Package | 1 - PS/2 KVM Cable |

| | |
|---------------------|---------------------------------|
| Package | |
| Included in Package | 1 - USB 2.0 Virtual Media Cable |
| Included in Package | 1 - USB KVM Cable |
| Included in Package | 1 - Rack Mount Kit |
| Included in Package | 1 - Software CD |
| Included in Package | 1 - Instruction Manual (on CD) |
| Included in Package | 1 - Quick Start Guide |

Certifications, Reports and Compatibility

