

## AXIS Q3617-VE Network Camera

Outstanding image quality with easy installation

Thanks to its 1/1.8" sensor and high-performance image processing, AXIS Q3617-VE supports Lightfinder and WDR - Forensic Capture with optimal image quality in difficult light conditions. It provides 4 MP at 30 fps with WDR, or 6 MP at 20 fps with WDR disabled. AXIS Q3617-VE offers a unique remote pan/tilt/roll/zoom (PTRZ) solution, easy conduit connection and cable management for minimized installation time. The PTRZ capability is also useful if the camera needs to be redirected. Robust and reliable, AXIS Q3617-VE is designed for harsh environments. Electronic image stabilization delivers steady images even during vibrations.

- > [Exceptional video quality with 1/1.8" sensor](#)
- > [Lightfinder and WDR - Forensic Capture](#)
- > [4 MP at 30 fps with WDR](#)
- > [Unique PTRZ capability for efficient installation](#)
- > [Axis' Zipstream technology](#)



# AXIS Q3617-VE Network Camera

<b>Camera</b>		<b>Data streaming</b>	Event data
<b>Image sensor</b>	Progressive scan RGB CMOS 1/1.8"	<b>Built-in installation aids</b>	Pan/tilt/roll: Designed to withstand at least 200 full cycles, Autoroll, Remote zoom, Remote focus, Pixel counter
<b>Lens</b>	Varifocal, 4.1–9 mm, F1.6 Horizontal field of view: 6 MP mode: 101°–46°, 4 MP 16:9 mode: 90°–41° Vertical field of view: 6 MP mode: 66°–30°, 4 MP 16:9 mode: 49°–23° Remote focus and zoom, P-Iris control, IR corrected	<b>General</b>	
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Casing</b>	IP66-, IP67-, IP6K9K- and NEMA 4X-rated, IK10 impact-resistant casing with polycarbonate dome, aluminum base and dehumidifying membrane Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
<b>Minimum illumination</b>	Color: 0.18 lux, F1.6; B/W: 0.03 lux, F1.6	<b>Sustainability</b>	PVC free
<b>Shutter time</b>	1/100000 s to 2 s	<b>Memory</b>	1 GB RAM, 256 MB Flash
<b>Camera angle adjustment</b>	Pan 370 degrees Tilt +/- 81 degrees Roll +/- 110 degrees	<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 6.1 W, max 11.4 W
<b>Video</b>		<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Resolutions</b>	3072x2048 to 160x90	<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
<b>Frame rate</b>	4 MP 16:9 (2720x1536) or 4:3 (2304x1728) with WDR: 25/30 fps with power line frequency 50/60 Hz 6 MP (3072x2048) without WDR: 20 fps	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis' Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	<b>Approvals</b>	EMC EN 55022 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, ISO 20653 IP6K9K, NEMA 250 Type 4X, IEC/EN 62262 IK10
<b>Multi-view streaming</b>	Up to 4 individually cropped out view areas	<b>Dimensions</b>	Depth: 166 mm (6 9/16 in) Depth with weather shield: 224 mm (8 13/16 in) ø 198 mm (7 13/16 in)
<b>Image settings</b>	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zone, WDR – forensic capture: Up to 120 dB depending on scene, Noise reduction, Fine tuning of behavior at low light, Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy mask, Mirroring of images, Electronic image stabilization, Barrel distortion correction	<b>Weight</b>	2.3 kg (5.1 lb) with weather shield
<b>Pan/Tilt/Zoom</b>	2.2x optical zoom and 2x digital zoom Digital PTZ Optical zoom and digital PTZ preset positions	<b>Included accessories</b>	AXIS Connector Guard A, Safety hook wire, Installation Guide, Windows decoder 1-user license, Resistor <sup>®</sup> L-key, Weather shield, Mounting bracket, Drill template, Cable gasket, Axis U-shape conduit adapter
<b>Network</b>		<b>Optional accessories</b>	AXIS T94V01L Recessed Mount, AXIS T94V01D Pendant Kit, AXIS T98A17-VE Cabinets, Axis Pole Mounts, Axis Ceiling Mounts, Axis Wall Mounts, AXIS T90B Illuminators, AXIS ACI Conduit Adapter 3/4" NPS, AXIS Q36-VE Smoked Dome, AXIS Surveillance microSDXC™ Card For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	<b>Video management software</b>	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>™</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>System integration</b>		<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>	<b>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</b>	
<b>Analytics</b>	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	<b>Environmental responsibility:</b>	<a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>
<b>Event triggers</b>	Analytics, Edge storage events, Shock detection		
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage, Pre- and post-alarm video buffering, Zoom or digital PTZ preset, Overlay text, Send SNMP trap		