

# TeraStation™ 5010

## Network Attached Storage



NAS with native  
10GbE connectivity.

Scalable high performance network storage for businesses.

Buffalo's TeraStation™ 5010 series has been built for small and medium sized businesses seeking an easy and cost-effective 10GbE platform. The TS5010 is a network attached storage (NAS) solution with iSCSI protocol designed to move SMB data at enterprise level speeds and eliminate the bottlenecks that can occur on slower networks.

Thanks to its powerful hardware the TS5010 series can run multiple concurrent services seamlessly with minimal performance degradation, and is ideal for organizations looking to add an affordable virtualized storage to their business network. Branch offices no longer need full-scale server infrastructure for simple tasks such as file sharing and backup.

In combination with Buffalo's 10GbE business switches the quad core processor featuring TS5010 reaches faster than ever data transfer speeds. The series comes populated with NAS- or enterprise nearline (TS51210RH) grade HDD and is available in 2-, 4- or 8-bay desktop and 4- or 12-bay rackmount configurations.

The 8- and 12-bay versions come fully populated or partially populated with four hard drives, thus giving companies the flexibility to start with a smaller initial investment and increase the total capacity when the need arises in the future. The 2-bay TS5210DF is equipped with SSDs and therefore highly shock-/vibration-proof and extremely fast.

## Features and Benefits

- High-speed native 10GbE connection (1 or 2 (TS51210RH only) 10GbE ports)
- 2.5/5Gbps compatible, compliant with NBASE-T (IEEE 802.3bz) standard
- Powered by the high performance Annapurna Labs® Quad-Core processor
- 4GB/8GB (TS51210RH) DDR3 ECC RAM
- Available in 2-bay, 4-bay and 8-bay desktop models or 4-bay and 12-bay rackmount
- Simultaneous NAS and iSCSI target functionality
- Advanced NTFS Permissions (Windows ACL)
- VMware certified
- Rapid RAID mode change
- RMM (RAID Mode Manager)
- TRIM Command for increased SSD life time (TS5210DF)
- AES 256bit data encryption
- Boot Authentication ensures the device is only accessible on authorized networks
- Data replication protection, Rsync compatible
- Integrated cloud backup with Dropbox, Dropbox Business and Amazon S3; remote access through WebAccess
- NovaStor backup software that provides server and workstation licensing
- Reduced system downtime with Duplex Firmware
- Active Directory (up to 10.000 supported users/groups imported from the domain)

## About Buffalo

Buffalo Technology is a leading global provider of award-winning storage, networking and multimedia solutions for the home and small business environments as well as for system builders and integrators. With more than four decades of networking and computer peripheral experience, Buffalo has proven its commitment to delivering innovative solutions that have put the company at the forefront of infrastructure technology.

# Specifications

Models	TS5210DF (2-bay)	TS5210DN (2-bay)	TS5410DN (4-bay)	TS5410RN (4-bay)	TS5810DN (8-bay)	TS51210RH (12-bay)
Part Numbers	TS5210DF00502-EU TS5210DF0202-EU	TS5210DN0402-EU TS5210DN0602-EU TS5210DN0802-EU TS5210DN1202-EU TS5210DN1602-EU	TS5410DN0804-EU TS5410DN1204-EU TS5410DN1604-EU TS5410DN2404-EU TS5410DN3204-EU	TS5410RN0804-EU TS5410RN1204-EU TS5410RN1604-EU TS5410RN2404-EU TS5410RN3204-EU	TS5810DN1604-EU TS5810DN3204-EU TS5810DN3208-EU TS5810DN6408-EU	TS51210RH0804-EU TS51210RH1604-EU TS51210RH2412-EU TS51210RH4812-EU TS51210RH9612-EU
Configuration	Desktop	Desktop	Desktop	Rackmount 19" 1U	Desktop	Rackmount 19" 2U
Total Capacities	512 GB, 2 TB	4, 6, 8, 12, 16 TB	8, 12, 16, 24, 32 TB	8, 12, 16, 24, 32 TB	16, 32, 64 TB	8, 16, 24, 48, 96 TB
Anti-Vibration	10-150Hz 6G					
<b>Internal Hard Drives</b>						
Type	SSD			NAS HDD		Nearline HDD
Number of Drives	2	2	4	4	8 (fully populated) 4 (partially populated)	12 (fully populated) 4 (partially populated)
Capacities	256 GB, 1 TB		2, 3, 4, 6, 8 TB		4, 8 TB	2, 4, 8 TB
Drive Interface				SATA 6 Gbps		
Supported RAID		JBOD/0/1			JBOD/0/1/5/6/10	
<b>USB Interface</b>						
Standard Compliance				USB 2.0/3.0		
Connector Type				A type		
Number of Ports		2 x USB 3.0		3 x USB 3.0		2 x USB 2.0, 2 x USB 3.0
Data Transfer Rates				480 Mbps / 5 Gbps		
<b>System / Performance</b>						
CPU			Annapurna Labs® Alpine-Processor AL314 (1.7 GHz Quad-Core)			
RAM			4 GB DDR3 with ECC			8 GB DDR3 with ECC
<b>Environmental &amp; Power</b>						
Power Unit	1	1	1	1	1	1 (2nd optional)
Power Consumption	Max. 85 W; average active: 30 W; average idle: 15 W; standby: 0.8 W	Max. 85 W; average active: 45 W; average idle: 32 W; standby: 0.8 W	Max. 85 W; average active: 56 W; average idle: 45 W; standby: 0.8 W	Max. 100 W; average active: 60 W; average idle: 46 W; standby: 0.7 W	Max. 150 W; average active: 108 W; average idle: 87 W; standby: 4.5 W	Max. 500 W; average active: 122 W; average idle: 100 W; standby: 3.9 W
Power Supply	Internal AC 100-240 V, Universal 50/60 Hz					
Operating Temperature	0° - 40°C					
Operating Humidity	10 - 85% non-condensing					
<b>Dimensions / Weight</b>						
Dimensions (WxHxD)	170 x 170 x 230 mm	170 x 170 x 230 mm	170 x 215 x 230 mm	430 x 44,3 x 430 mm	300 x 215 x 230 mm	481 x 88 x 736.9 mm
Weight	3.5 kg	4.8 kg	7 kg	8.4 kg	12.5 kg	20 kg (main unit with 4 HDDs) 25 kg (main unit with 12 HDDs)
<b>LAN Interface</b>						
Standards Compliance	(10BASE-T) IEEE802.3, (100BASE-TX) IEEE802.3u, (1000BASE-T) IEEE802.3ab, (10GBASE-T) IEEE802.3an, (NBASE-T) IEEE802.3bz					
Number of Ports	1 (10GBASE-T), 2 (1GBASE-T)					2 x 10GBASE-T, 2 x 1GBASE-T
Data Transfer Rates	2.5/5/10 Gbps / 10/100/1000 Mbps					
Supported Protocols	TCP/IP					
Network File Services	CIFS/SMB, AFP, FTP, SFTP, NFS, SNMP					
Connector Type	RJ-45					
<b>Other</b>						
Client OS Support	Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008, Mac® OS® X 10.9 or later					
Included Software	NAS Navigator 2, NovaBACKUP® Buffalo Edition (one server and ten workstation licenses)					
Box Contents	TeraStation™, Quick Setup Guide, Cat 6a Ethernet Cable, AC Cable, Front Panel Key or Rail Kit with Mounting Brackets and Screws and Warranty Statement					
<b>Accessories</b>						
Compatible Hard Drives	OP-SSD256G, OP-SSD1.0	OP-HD2.0N, OP-HD3.0N, OP-HD4.0N, OP-HD6.0N, OP-HD8.0N			OP-HD4.0N, OP-HD8.0N	OP-HD2.0H2U, OP-HD4.0H2U, OP-HD8.0H2U
Redundant Power Unit						OP-PU-10R2U



© Buffalo Inc. 2017.

BUFFALO logo, AirStation, Nfiniti, AOSS, TeraStation, LinkStation, DriveStation and MiniStation are either trademarks or registered trademarks of Melco Holdings Inc. or Buffalo Inc. Microsoft Windows and Microsoft logo are either registered trademarks or trademarks of Microsoft Corporation in United States and/or other countries. The names and logos of other companies mentioned herein belong to their respective owners. The information within this datasheet is subject to change without notice. All rights reserved. E & OE.