



## 8-Port Rackmount LCD Console KVM Switch

17-Inch LCD Panel, PS/2 or USB, 1U, connection cables included

Part No.: **506540**

Convenient access and control.

The INTELLINET NETWORK SOLUTIONS Model 506540 8-Port Rackmount Console KVM Switch allows easy and convenient access to eight servers while allowing full control from a single device.

### Easy and Convenient

With the industry-standard 19" 1U-height rack drawer, the Rackmount Console KVM Switch can be easily pulled out and accessed in the extended position, and the display can be folded down, locked and secured when stored.

### Full Functionality

With superior KVM functionality, you can manage and control eight PS/2 or USB computers from this single device.

### Features:

- Integrated LCD console, keyboard, mouse, and KVM switch module for rack-mount installation
- Manage/control 8 PS/2 or USB computers from one keyboard, monitor and mouse
- Includes eight 1.8 m (6 ft.) connection cables for PS/2 or USB computers
- Standard 19 inch 1U rack drawer
- Gain complete control with easy-to-use OSD interface
- Flip-open 17 inch LCD panel (2048 x 1536 highest resolution; 1280 x 1024 optimal resolution)
- Adjustable - for rack cabinets with depths from 600 mm to 1200 mm (23.6 to 47 in.)
-

- » PC port connectors:
  - Keyboard + mouse + monitor: HD15 x 8
- » Console port connectors:
  - Keyboard: PS/2 & USB
  - Mouse: PS/2 & USB
  - Monitor: HD15 female
- » Computer selection:
  - Via buttons
  - Via hotkeys
- » OSD: yes
- » Video resolution: max. 2048 x 1536
- » Video bandwidth: 300 MHz
- » FCC Class B, CE, RoHS

**Power**

- » Power input (AC): approx. 100 - 240 V
- » MTBF: 60,000 hours

**LCD Panel**

- » Active display area: 337.9 x 270.3 (mm)
- » Pixel pitch: 0.264 (H) x 0.264 (W)
- » Resolution: 2048 x 1536 @ 60 Hz; 1280 x 1024 @ 75 Hz
- » Brightness: 250 (Typ)
- » Contrast ratio: 400:1 (Typ)
- » Display color: 16.2 M colors
- » User control: OSD control (auto saving)
- » Backlight unit: 4-CCFL type
- » MTBF: 50,000 hours

**Environmental**

- » KVM module dimensions: 42 (H) x 446 (W) x 636 (D) mm (1.6 x 17.5 x 25 in.)
- » Weight: 20.6 kg (45.4 lbs.)
- » Operating temperature: 0 – 50°C
- » Storage temperature: -20 – 60°C (-4 – 140°F)

**Package Contents**

- » 8-Port Rackmount Console KVM Switch
- » Rear bracket and extension kit
- » KVM switch module
- » Power adapter
- » Eight 1.8 m (6 ft.) PS/2 and USB combo cables
- » KVM Switch Module user manual



