

Voice Cabling Products

CW1308B Internal/External Phone Cable

CW1308B telephone cables are suitable for the internal or external connection of telephone systems and other communications equipment.

The cables are insulated and sheathed in LSZH, making them an extremely cost effective general signal cable for fixed installation. The standard sheath colour is black and other pairs are available.



Features & Benefits

- Conforms to BT Specification
- Stocked in 10, 20, 50 & 100 pairs
- Other pairs available upon request

Ordering Information

Product Description	Part Number
CW1308B 10 Pair Phone Cable + Earth	001-008-004-10E
CW1308B 20 Pair Phone Cable + Earth	001-008-004-20E
CW1308B 50 Pair Phone Cable + Earth	001-008-004-50E
CW1308B 100 Pair Phone Cable + Earth	001-008-004-100E

Product Specifications

Conductor Diameter	0.5 mm
Earth Core Diameter	1.38 mm
Max. Conductor Resistance at 20°C	97.8 ohm/km
Min. Insulation Resistance at 20°C	50 Megaohms/km
Max. Capacitance Unbalanced	500pF/Km
Working Temperature	0°C to + 70°C
Min. Bend Radius - Fixed	8 x cable diameter
Sheath Colour	Black LSZH
Insulation	PVC (Polyvinyl chloride)

Pair Specifications

Pairs	10+E	20+E	50+E	100+E
Approx Overall Diameter (mm)	7.0	9.0	13.5	19.0
Weight (kg/km)	98	155	325	610