



Televés reserves the right to modify the product

AVANT X Basic programmable multiband amplifier for terrestrial signals, with AutoLTE

32 digital programmable filters (ASuite or universal programmer)

A new evolutionary stage

Multi-input multiband amplifier, perfect for terrestrial individual or MDU (Multi Dwelling Unit) installations, that allows programming up to 32 digital filters on 4 VHF+UHF inputs (DTT).

The multiband amplifier is equipped with 5 inputs: FM-4xVHF/UHF, and can achieve programmable amplification and balancing of the different RF inputs.

Thanks to ASuite, the multiband amplifier programming is very easy and intuitive using an Android or Windows application.

The multiband amplifier is able to detect LTE signals and automatically set the filter to channel 48 (for LTE700) or 60 (for LTE790), thanks to the automatic LTE filtering.

RED compliant

Ref.532101

Art.Nr	AVANTXBASIC
EAN13	8424450201435

Highlights

- Digital processing technology implemented on terrestrial TV signals
- Up to 32 individually programmable filters: single channel digital filtering, even for adjacent channels (1 to 4 channels)
- Digital processing of channels: output channels can be frequency shifted
- Automatic signal adjustment in each filter (AGC): and output signal manual regulation
- UHF/VHF digital filters with high selectivity: 30dB rejection (@ 1MHz)
- AutoLTE: automatic internal adaptation of filters, depending on the LTE signal type (4G/5G)

- SAW filters (Surface Acoustic Wave) against LTE interferences, with the best selectivity and stability
- Compatible with DVB-T and DVB-T2
- TForce Technology: terrestrial signal level always stable and adapted to its optimum value
- Storage of several setups and cloning between different AVANT X models
- Zamak chassis provides high screening effect
- Light-weight and compact multiband amplifier with a wide range of features (225x120x55mm)
- Very easy configuration and adjustment using ASuite application for Android or Windows

Main features

- All the inputs support UHF and VHF
- Automatic balancing according to the programmed output level and equalization slope
- High output power
- Allocation of filters to inputs without restraints
- Powering of pre-amplifiers or BOSS system
- LED indicators displaying both unit and signal statuses
- Easy-to-replace power supply

Discover

Avant X: A new evolutionary stage

Avant X is a full range of digital programmable multiband amplifiers, which main mission is to achieve a programmable amplification and balance of different RF input signals.

- VHF+UHF inputs: the channels present in these inputs can be filtered and adjusted using up to 32 digital filters. Each filter can be tuned to any VHF+UHF channel, and its bandwidth can comprise between 1 and 4 channels. The arrangement of the 32 filters is configurable based on the number of channels present on each VHF+UHF input. It's compatible with DVB-T and DVB-T2. The output level is programmable between 90-115dB μ V for one-output options (BASIC and PRO), and between 86-111dB μ V for two-output options (BASIC SAT and PRO SAT). Furthermore, an equalization slope of up to 5 dB can be programmed at the output.
- The FM input can be enabled or not. In case this input is enabled, it will be amplified and its output level set to 10 dB below the lowest-level UHF channel (taking into account the equalization slope).
- IF input (only for models equipped with SAT): satellite input can be assigned an attenuation between 0 dB and 30dB, and an equalization between 0 dB and 15dB. The LNB can be configured to be REMOTELY (user STB) or LOCALLY powered by enabling the 22 kHz tone and configuring the supply voltage value to 13 or 17 V.

Choose the desired programming mode...

Avant X provides three different programming options:

- App ASuite for PC or tablet / Android smartphone, via USB connection (OTG cable included): The multiband amplifier configuration is performed in a friendly and intuitive environment. A configuration can be defined and stored - even without being connected to the multiband amplifier - only to retrieve it at installation and adjustment time.
Furthermore, for PRO versions, the application allows the monitoring of the quality parameters and the production of an installation report describing the configuration used.
- Universal programmer (ref. 7234): The unit is compatible with the programmer, ensuring backwards compatibility.
- Automatic programming by means of the "AUTO-PROGRAMMING" button (press and hold) of the multiband amplifier itself (PRO versions only): Thanks to a tuner that is able to detect DVB-T/T2 channels for UHF+VHF inputs, the unit performs an automatic programming of the filters when executing this option, as well as the appropriate tuning to avoid intermodulation.

By pressing the READJUST button (short press), the unit is readjusted to the stored configuration values.
After the multiband amplifier is adjusted, a manual fine tuning can be performed to slightly correct the VHF/UHF and FM filters' gain.

Technical specifications

Inputs			VHF+UHF	FM
Nr. of inputs			4	1
Frequency range	MHz	174 - 230	470 - 694 / 790 (automatic LTE)	87 - 108
Maximum gain	dB		75	29
Nr. of filters			32	-
Nr. of channels per filter			1...4	-
Filter configuration			No restraints	-
Slope regulation	dB	-	0 - 5	-
Recommended input margin	dB μ V	40 - 100	40 - 100	76 - 101
Gain regulation	dB		0 - 30 (auto)	0 - 25 / OFF
Manual regulation after auto-adjustment	dB		+/- 3	+/- 5
Output level (DIN45004B)	dB μ V		122	
Output level (EN50083 IMD3 2CH -36dB)	dB μ V		126	
Programmable output level	dB μ V	87-112	90-115	80-105
Selectivity	dB		>30@+/-1MHz	>20 @+/-20MHz
Input powering	Vdc		12 (AUTO/ON/OFF)	-
Maximum current per input	mA		50	
Mains voltage / frequency	Vac / Hz		220 - 230 / 50 - 60	
Total consumption	W		14	
Maximum operating temperature	°C		45	
Weight	gr		920	
Dimensions	mm		225x120x55	
Protection index	IP		20	