

TELENCO® HYPOCUT FIBRE OPTIC DROP CLAMP



Part of the Telenco® HYPOCLAMP family, the HYPOCUT clamp enables the anchoring of flat aerial drop cables where spans do not exceed 70m. This clamp consists of a stainless steel body, a shim with an embedded blade and a plastic wedge equipped with an integrated opening bail. For easy cable installation, the Telenco® HYPOCUT clamp is delivered in 2 parts.

FEATURES & BENEFITS

- | |
|--|
| Easy, quick and tool-less installation |
| Opening bail for installation onto closed or opened hardware: cross-arms, hooks, brackets (min. Ø11mm) |
| Installation without cable bending into the clamp |
| Effective grip on 3x6 Commscope® EZ AXS & Corning® ROC drop cables |

PERFORMANCES

This clamp is fully compliant with the following international standards:

- NF EN C-20-540 Climatic ageing test
- NF EN 60068-2- 11 and ASTM B117 Corrosion test
- XP C93-850-3-25 §4.3.5 and §4.3.6 for tensile and aeolian test

INSTALLATION

- | |
|---|
| On end poles |
| When the line is at an angle greater than 25° in order to preserve the integrity of the cable over time |
| If road crossing (mandatory cable stop on each pole both sides of the road) |
| In case of unbalanced adjacent spans (a span of 40m, followed by a span of 30m, for example) |
| If a rugged terrain (line mountainside down for example) |
| In alignment, every 5 poles or on every pole |

