

SC/APC – SC/APC Dual Sheathed Patch Leads

Commonly used widely in applications such as FTTx, gigabit passive optical network (GPON) and wavelength-division multiplexing (WDM), Connectix OS2 singlemode SC/APC –SC/APC patch leads are manufactured using bend insensitive G.657.A1 or G.675.A2 optical fibre, terminated with standards compliant connectors and 100% tested and certified.

The dual sheathed FTTx patch leads provide a consumer end solution, interconnecting an outdoor connection to an indoor distribution point. Manufactured using an outer UV-resistant black low smoke zero halogen sheath (LSZH) for external use which can then be easily stripped back to reveal an inner LSZH white sheath suitable for a short indoor run. Multiple layers of Kevlar strengthening members help ensure the cable remains robust for FTTX installations.

Available in standard, premium and premium low-loss Senko connector formats the SC/APC connector is a zirconia ceramic ferrule with choice of endface types including standard, step, and cone. These endface types allow for faster polishing, and lower insertion loss and back reflection when terminated within Connectix and Senko production procedures, while ensuring maximum repeatability.

The connector body is precision moulded and available in 900µm as standard or 2.0mm long boot or 3.0mm long boot formats. The housing and boot are made from UL-rated material and Physical Contact (PC) version is also available.

Features & Benefits

- Compliance with Telcordia, ANSI, IEC, TIA, NTT and JIS specifications
- Low insertion loss & back reflection
- One-piece construction & pull-proof design
- Free-floating ceramic ferrule
- Precision anti-rotation key and corrosion resistant body
- UL-rated plastic housing and boots in a variety of colours
- Telcordia style boots
- Adapters with choice of metal or plastic housing, mount styles & flange options



Technical Parameters										
Cable Count	Outside Diameter (mm)	Buffer Diameter (mm)	Weight (kg)	Minimum Allowable Tensile Strength (N)		Minimum Allowable Crush Load (N/100mm)		Minimum Bending Radius (mm)		Storage Temperature (°C)
				Short Term	Long Term	Short Term	Long Term	Short Term	Long Term	
1	4.5	0.9	15	300	150	300	150	20D	10D	-20+60
2	4.5	0.9	15	300	150	300	150	20D	10D	-20+60

Product Series	IL Against Master (dB)		IL Random Mating (dB)	
	Average IL	Maximum IL	Mean IL	Maximum IL
Premium Low Loss APC	0.07	0.15	0.09	0.20
Premium APC	0.10	0.25	0.14	0.30

SC/APC – SC/APC Dual Sheathed Patch Leads

Singlemode	
Operating Temperature	-40°C to + 75°C
Durability	<0.1dB typical change, 500 matings*

IEC Random mating test IEC 61753-1

1. To meet IEC Random Mating Grade A (≤ 0.07 dB mean, ≤ 0.15 dB max for >97% of sample)
Grade A Spec is not finalised, above is a recommendation
2. To meet IEC Random Mating Grade B (≤ 0.12 dB mean, ≤ 0.25 dB max for >97% of sample)
3. To meet IEC Random Mating Grade C (≤ 0.25 dB mean, ≤ 0.50 dB max for >97% of sample)

Ordering Information	
Product Description	Part Number
Connectix OS2 Singlemode Simplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead	005-050-xxx-01
Connectix OS2 Singlemode Simplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead Premium Loss	005-051-xxx-01
Connectix OS2 Singlemode Simplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead Premium Low Loss	005-052-xxx-01
Connectix OS2 Singlemode Duplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead	005-060-xxx-01
Connectix OS2 Singlemode Duplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead Premium Loss	005-061-xx-01
Connectix OS2 Singlemode Duplex SC/APC – SC/APC LSZH Dual Sheathed FTTX Patch Lead Premium Low Loss	005-062-xxx-01

[xxx = denotes metre length]

005 = 0.5 metre

010 = 1 metre

100 = 10 metre

[Singlemode fibre type confirmed at time of quote/order, i.e G.657.A1 or G.657.A2]