


Multimode Fibre Optic Pigtails

Connectix fibre optic pigtails are typically used to link the fibre optic cable with fibre optic equipment. The connector side of the pigtail is used to link the equipment, while the other side is fusion spliced together with the fibre cable. By splicing together the fibre glasses, it can reach a minimum insertion loss.

We are committed to holding extensive stock of many assembly types in all common lengths. This allows us to provide a same day despatch service on most small or medium volume orders.

Features & Benefits

- LC, SC, ST and FC available from stock
- E2000, ESCON, FDDI, MU & MTRJ available within minimal time-frame
- Individually bagged with individual test certificates
- Can be labelled and packaged to your requirements



Product Specifications	
Fibre Type	900µm tight buffered
Length	1.0m +/- 10 mm Other lengths available to order
Sheath Colour	White/Orange/Aqua Other colours available to order
Fire Performance	LSZH applications flame resistance IEC 60332-1
Connector Specification	Compliant with IEC 874-14
Ferrule Material	Full zirconia
Insertion Loss	Max. 0.3dB typical 0.2dB
Return Loss	> -40dB
Operating Temperature	-40°C to +85°C

Ordering Information	
Product Description	Part Number
LC Pigtail 62.5/125 1 Metre	005-102-010-01B
SC Pigtail 62.5/125 1 Metre	005-107-010-01B
ST Pigtail 62.5/125 1 Metre	005-101-010-01B
LC Pigtail 50/125 1 Metre	005-422-010-01B
SC Pigtail 50/125 1 Metre	005-407-010-01B
ST Pigtail 50/125 1 Metre	005-401-010-01B
LC Pigtail OM3 1 Metre	005-424-010-01B
SC Pigtail OM3 1 Metre	005-420-010-01B
ST Pigtail OM3 1 Metre	005-421-010-01B
LC Pigtail OM4 1 Metre	005-417-010-01B

For core specification please refer to Fibre Specification data sheet.