

## Cisco 2-Port and 4-Port OC-3c/STM-1c POS Shared Port Adapters

The Cisco® I-Flex approach combines shared port adapters (SPAs) and SPA interface processors (SIPs), providing an extensible design that enables service prioritization for data, voice, and video services. Enterprise and service provider customers can take advantage of improved slot economics resulting from modular port adapters that are interchangeable across Cisco routing platforms. The I-Flex design maximizes connectivity options and offers superior service intelligence through programmable interface processors that deliver line-rate performance. I-Flex enhances speed-to-service revenue and provides a rich set of quality of service (QoS) features for premium service delivery while effectively reducing the overall cost of ownership. This data sheet contains the specifications for the Cisco 2-Port and 4-Port OC-3c/STM-1c POS SPAs (Cisco 2- and 4-Port OC-3 POS SPAs; refer to Figure 1).

**Figure 1.** Cisco 2- and 4-Port OC-3 POS SPAs



### Product Overview

The Cisco 2- and 4-Port OC-3 POS SPAs are available on high-end Cisco routing platforms, offering the benefits of network scalability with lower initial costs and easy upgrades. The Cisco SPA/SIP portfolio continues Cisco's focus on investment protection along with consistent feature support, broad interface availability, and the latest technology. The Cisco SPA/SIP portfolio allows deployment of different interfaces (packet over SONET/SDH [POS], ATM, Ethernet, etc.) on the same interface processor.

The Cisco 2- and 4-Port OC-3 POS SPAs are available with two or four Small Form-Factor Pluggable (SFP) interfaces. SFP modules are available in multiple optical reaches from 2 to 80 kilometers (km).

### Key Features and Benefits

The Cisco SPA/SIP portfolio offers many advantages, including:

- Highly modular, flexible, intelligent interface processors

- Superior flexibility, providing a combination of interface types on the same interface processor for consistent services, independent of access technology.
- Pioneering programmable interface processors that provide flexibility for the service diversity required in next-generation networks.
- Innovative design that supports intelligent service delivery without compromising on performance.
- Increased speed to service revenue
  - The scalable, programmable Cisco architecture extended to 10 Gbps dramatically improves customer density, increasing potential revenue per platform.
  - Interface breadth (copper, channelized, POS, ATM, and Ethernet) on a modular interface processor allows service providers to roll out new services more quickly, helping ensure that all customers large and small receive consistent, secure, and guaranteed services.
  - High-density SFP interfaces are featured for high-port-count applications with reach flexibility. Future optical technology improvements can be adopted using existing SPAs.
- Dramatically improved return on your routing investment
  - Improved slot economics and increased density reduce capital expenditures (CapEx).
  - The ability to easily add new interfaces as they are needed enables a "pay-as-you-grow" business model.
  - SPAs are shared across multiple platforms, and can be easily moved from one to another, providing consistent feature support, accelerated product delivery, and a significant reduction in operating expenses (OpEx) through common sparing as service needs change.

## Product Specifications

Table 1 gives specifications of the Cisco 2- and 4-Port OC-3 POS SPAs.

**Table 1.** Product Specifications

Features	Descriptions
<b>Product Compatibility</b>	Cisco 7304 Router Cisco Catalyst 6500 Series Switches Cisco 7600 Series Routers Cisco CRS1 (4-port OC-3 POS SPA)
<b>Port Density per SPA</b>	2 ports 4 ports
<b>Physical Interface</b>	OC-3c/STM-1c SFP optics module (refer to optical parameters in Table 2) Visual status indicators (LEDs): <ul style="list-style-type: none"> <li>• SPA status LED</li> <li>• Per-port LEDs</li> <li>• Carrier and alarm</li> <li>• Active and loopback</li> </ul>
<b>Protocols</b>	High-Level Data Link Control (HDLC), RFC 2615 Point-to-Point Protocol (PPP), RFC 1662 Frame Relay, RFC 2427 IPv4/IPv6

<b>Features and Functions</b>	<p>Synchronization</p> <ul style="list-style-type: none"> <li>• Local (internal) or loop timed (recovered from network)</li> <li>• Pointer activity monitoring</li> </ul> <p>Local (diagnostic) and line (network) loopback</p> <p>Section data communications channel (SDCC) – platform-dependent feature</p> <p>Payload mapping</p> <ul style="list-style-type: none"> <li>• POS with 1 + x<sup>43</sup> self-synchronous scrambler</li> </ul> <p>SONET/SDH compliance</p> <ul style="list-style-type: none"> <li>• Telcordia (Bellcore) GR-253-CORE (as applicable)</li> <li>• ANSI T1.105 and T1.231</li> <li>• ITU-T G.707, G.957, and G.825 (as applicable)</li> </ul> <p>Supported SONET/SDH alarm and signal events:</p> <ul style="list-style-type: none"> <li>• Signal failure bit error rate (SF-ber)</li> <li>• Signal degrade bit error rate (SD-ber)</li> <li>• Signal label payload construction (C2)</li> <li>• Path trace byte (J1)</li> </ul> <p>Section</p> <ul style="list-style-type: none"> <li>• Loss of signal (LOS)</li> <li>• Loss of frame (LOF)</li> <li>• Error counts for B1</li> <li>• Threshold crossing alarms (TCA) for B1</li> </ul> <p>Line</p> <ul style="list-style-type: none"> <li>• Line alarm indication signal (LAIS)</li> <li>• Line remote defect indication (LRDI)</li> <li>• Line remote error indication (LREI)</li> <li>• Error counts for B2</li> <li>• TCA for B2</li> </ul> <p>Path</p> <ul style="list-style-type: none"> <li>• Path alarm indication signal (PAIS)</li> <li>• Path remote defect indication (PRDI)</li> <li>• Path remote error indication (PREI)</li> <li>• Error counts for B3</li> <li>• TCA for B3</li> <li>• Loss of pointer (LOP)</li> <li>• Positive stuffing event (PSE)</li> <li>• Negative stuffing event (NSE)</li> <li>• Path unequipped indication signal (PUNEQ)</li> <li>• Path payload mismatch indication signal (PPLM)</li> </ul>
<b>Network Management</b>	<p>RFC 2558 MIB (SONET/SDH)</p> <p>Simple Network Management Protocol (SNMP)</p>
<b>Reliability and Availability</b>	<p>Online insertion and removal (OIR)</p> <p>Field-replaceable SFP optical modules</p> <p>1 + 1 SONET automatic-protection-switching (APS) and SDH linear multiplex-section-protection (MSP) protocols</p> <p>Single SPA software reset</p>
<b>Physical Specifications</b>	<p>Weight: 0.75 lb (0.34 kg)</p> <p>Height: 0.8 in. (2.03 cm) (single height)</p> <p>Width: 6.75 in. (17.15 cm)</p> <p>Depth: 7.28 in. (18.49 cm)</p>
<b>Power</b>	<p>2-port OC-3c/STM-1c = 13W maximum (no optics)</p> <p>4-port OC-3c/STM-1c = 14W maximum (no optics)</p>
<b>Environmental Specifications</b>	<p>Operating temperature: 41 to 104°F (5 to 40°C)</p> <p>Storage temperature: –38 to 150°F (–40 to 70°C)</p> <p>Operating humidity: 5 to 85% relative humidity</p> <p>Storage humidity: 5 to 95% relative humidity</p>

<b>Compliance and Agency Approvals</b>	<p>Safety</p> <ul style="list-style-type: none"> <li>• UL 60950</li> <li>• CSA 22.2-No.60950</li> <li>• EN60950</li> <li>• IEC 60950 CB Scheme</li> <li>• ACA TS001</li> <li>• AS/NZS 3260</li> <li>• EN60825\IEC60825 laser safety (SR, IR-Class 1) (VSR-Class 1M)</li> <li>• 21CFR1040 - FDA Code of Federal Regulations (USA) laser safety (SR, IR-Class 1) (VSR-Class 1M)1</li> </ul> <p>EMC</p> <ul style="list-style-type: none"> <li>• FCC Part 15 (CFR 47)</li> <li>• ICES 003</li> <li>• EN55022</li> <li>• CISPR 22</li> <li>• AS/NZ 3548</li> <li>• VCCI</li> <li>• EN55024</li> <li>• EN50082-1</li> <li>• EN61000-6-1</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> </ul> <p>Network Equipment Building System (NEBS) This product is designed to meet the following requirements (official qualification may be in progress):</p> <ul style="list-style-type: none"> <li>• SR-3580 - NEBS: Criteria levels (Level 3 compliant)</li> <li>• GR-63-Core - NEBS: Physical protection</li> <li>• GR-1089-Core - NEBS: EMC and safety</li> </ul> <p>ETSI</p> <ul style="list-style-type: none"> <li>• EN300 386/EN300 386-2 Class B</li> <li>• ETS 300 019 Storage Class 1.1</li> <li>• ETS 300 019 Transportation Class 2.3</li> <li>• ETS 300 019 Stationary Use Class 3.1</li> </ul>
--	--

Table 2 gives optical specifications of the Cisco 2- and 4-Port OC-3 POS SPAs.

**Table 2.** OC-3c/STM-1c POS Optical Specifications

SFP Optics	Maximum Distance
<b>Multimode (MM) Short Reach (SR)</b>	Up to 1.2 mi (2 km)
<b>Single-Mode (SM) SR</b>	Up to 1.2 mi (2 km)
<b>SM Intermediate Reach (IR-1)</b>	Up to 9 mi (15 km)
<b>SM Long Reach (LR-1)</b>	Up to 25 mi (40 km)
<b>SM Long Reach (LR-2)</b>	Up to 50 mi (80 km)

## Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#) or refer to Table 3.

**Table 3.** Ordering Information

Product Name	Part Number
<b>Cisco 2-Port OC-3c/STM-1c POS Shared Port Adapter</b>	SPA-2XOC3-POS
<b>Cisco 4-Port OC-3c/STM-1c POS Shared Port Adapter</b>	SPA-4XOC3-POS
<b>OC-3/STM-1 SFP, MM, SR</b>	SFP-OC3-MM
<b>OC-3/STM-1 SFP, SM, SR</b>	SFP-OC3-SR
<b>OC-3/STM-1 SFP, SM, IR-1</b>	SFP-OC3-IR1

OC-3/STM-1 SFP, SM, LR-1	SFP-OC3-LR1
OC-3/STM-1 SFP, SM, LR-2	SFP-OC3-LR2

## Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, refer to [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

## For More Information

For more information about the Cisco SPA/SIP portfolio, visit <http://www.cisco.com/go/spa> or contact your local Cisco account representative.



**Americas Headquarters**  
 Cisco Systems, Inc.  
 170 West Tasman Drive  
 San Jose, CA 95134-1706  
 USA  
[www.cisco.com](http://www.cisco.com)  
 Tel: 408 526-4000  
 800 553-NETS (6387)  
 Fax: 408 527-0883

**Asia Pacific Headquarters**  
 Cisco Systems (USA) Pte. Ltd.  
 168 Robinson Road  
 #28-01 Capital Tower  
 Singapore 068912  
[www.cisco.com](http://www.cisco.com)  
 Tel: +65 6317 7777  
 Fax: +65 6317 7799

**Europe Headquarters**  
 Cisco Systems International BV  
 Haarlerbergpark  
 Haarlerbergweg 13-19  
 1101 CH Amsterdam  
 The Netherlands  
[www-europe.cisco.com](http://www-europe.cisco.com)  
 Tel: +31 0 800 020 0791  
 Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, IQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0710R)