

CISCO SFP OPTICS FOR PACKET-OVER-SONET/SDH AND ATM APPLICATIONS

The Cisco industry-standard Small Form-Factor Pluggable Interface Converter (SFP) for packet-over-SONET/SDH (POS), optical networking, and ATM applications (Figure 1) are hot-swappable optical interfaces that plug into a variety of ports on Cisco router interfaces. These SFP optics support OC-3, OC-12, and OC-48 data rates for multimode, short-reach, intermediate-reach, and long-reach applications.

Figure 1. Cisco SFP Optics for POS/SDH and ATM Applications



PRODUCT OVERVIEW

Cisco® SFP optics for POS and ATM applications plug into a variety of SFP-based POS, TDM and ATM interfaces on Cisco router products. This line of SFP optics supports the following three data rates at various reaches: OC-3/STM-1 (155 Mbps), OC-12/STM-4 (622 Mbps), and OC-48/STM-16 (2,488 Gbps) (Table 1).

The SFPs are compatible with the SONET/SDH and ATM standards, and support the digital diagnostic functions specified in the SFF-8742 Multi-Source Agreement (MSA) and the extended operating temperature range from 23 to 185°F (-5 to 85°C).

Table 1. Features

Product Description	Typical Distance (km)	Fiber Type	Temperature Range (°C)	Digital Optical Monitoring Support
SFP OC-3/STM-1 Multimode	2	multimode	-5 to +85	Yes
SFP OC-3/STM-1 Short Reach	2	single mode	-5 to +85	Yes
SFP OC-3/STM-1 Intermediate-Reach	15	single mode	-5 to +85	Yes
SFP OC-3/STM-1 Long-Reach (40 km)	40	single mode	-5 to +85	Yes
SFP OC-3/STM-1 Long-Reach (80 km)	80	single mode	-5 to +85	Yes

Product Description	Typical Distance (km)	Fiber Type	Temperature Range (°C)	Digital Optical Monitoring Support
SFP OC-12/STM-4 Multimode	0.5	multimode	-5 to +85	Yes
SFP OC-12/STM-4 Short-Reach	2	single mode	-5 to +85	Yes
SFP OC-12/STM-4 Intermediate-Reach	15	single mode	-5 to +85	Yes
SFP OC-12/STM-4 Long-Reach (40 km)	40	single mode	-5 to +85	Yes
SFP OC-12/STM-4 Long-Reach (80 km)	80	single mode	-5 to +85	Yes
SFP OC-48/STM-16 Short-Reach	2	single mode	-5 to +85	Yes
SFP OC-48/STM-16 Intermediate-Reach	15	single mode	-5 to +85	Yes
SFP OC-48/STM-16 Long-Reach (80 km)	80	single mode	-5 to +85	Yes

Note: The temperature is intended as the case temperature on the SFP (not the ambient temperature).

DIGITAL DIAGNOSTIC FUNCTIONS

The Cisco SFP optics for POS and ATM applications allow real-time access, through the digital diagnostic monitoring interface, to a set of transceiver parameters such as optical output power, optical input power, temperature, laser bias current, and transceiver supply voltage.

The ability to read these parameters in real time greatly enhances the installation, activation, and troubleshooting of these SFP optics.

PRODUCT SPECIFICATIONS

Tables 2 through 4 list the optical parameters for the Cisco SFP optics for POS and ATM applications.

Table 2. Optical Parameters for Cisco OC-3/STM-1 SFP

OC-3/STM-1 SFP	Transmitter Wavelength Range (nm)	Transmit Power Range (dBm)	Receiver Power Range (dBm)	Optical Path Penalty (dB)
Multimode	1270 to 1380	-14 to -19	-5 to -30	-
Short Reach	1260 to 1360	-8 to -15	-8 to -23	1
Intermediate Reach	1261 to 1360	-8 to -15	-8 to -28	1
Long Reach (40 km)	1263 to 1360	0 to -5	-10 to -34	1
Long Reach (80 km)	1480 to 1580	0 to -5	-10 to -34	1

Table 3. Optical Parameters for Cisco OC-12/STM-4 SFP

OC-12/STM-4 SFP	Transmitter Wavelength Range (nm)	Transmit Power Range (dBm)	Receiver Power Range (dBm)	Optical Path Penalty (dB)
Multimode	1270 to 1380	-14 to -20	-6 to -26	-
Short Reach	1261 to 1360	-8 to -15	-8 to -23	1

OC-12/STM-4 SFP	Transmitter Wavelength Range (nm)	Transmit Power Range (dBm)	Receiver Power Range (dBm)	Optical Path Penalty (dB)
Intermediate Reach	1293 to 1334	-8 to -15	-8 to -28	1
Long Reach (40 km)	1280 to 1335	+2 to -3	-8 to -28	1
Long Reach (80 km)	1480 to 1580	+2 to -3	-8 to -28	1

Table 4. Optical Parameters for Cisco OC-48/STM-16 SFP

OC-48/STM-16 SFP	Transmitter Wavelength Range (nm)	Transmit Power Range (dBm)	Receiver Power Range (dBm)	Optical Path Penalty (dB)
Short Reach	1266 to 1360	-3 to -10	-3 to -18	1
Intermediate Reach	1260 to 1360	0 to -5	0 to -18	1
Long Reach (80 km)	1500 to 1580	+3 to -2	-9 to -28	2

Connectors and Cabling

Connectors: Dual LC/PC connector

Note: Only connections with patch cords with PC or UPC connectors are supported. Patch cords with APC connectors are not supported.

ENVIRONMENTAL SPECIFICATIONS

- Extended operating case temperature range: 23 to 185°F (-5 to 85°C)
- Storage temperature range: 23 to 185°F (-5 to 85°C)

DIMENSIONS

- Dimensions (H x W x D): 8.6 mm x 13.7 mm x 56.5 mm

REGULATORY AND STANDARD COMPLIANCE

- Class 1 Laser per IEC60825-1 and CFR 21, Part 1040.01
- Optical Specification according to GR-253, ITU G.957, and G.707
- Optical Specification for SFP-OC3-MM ATM User-Network Interface Specification (v3.1)

ORDERING INFORMATION

To place an order, visit the [Cisco Ordering Home Page](#). Table 5 lists the ordering information for the Cisco SFP transceivers for POS/SDH and ATM applications.

Table 5. Ordering Information

Product Description	Part Number
SFP OC-3/STM-1 Multimode	SFP-OC3-MM
SFP OC-3/STM-1 Short-Reach	SFP-OC3-SR
SFP OC-3/STM-1 Intermediate-Reach	SFP-OC3-IR1

Product Description	Part Number
SFP OC-3/STM-1 Long-Reach (40 km)	SFP-OC3-LR1
SFP OC-3/STM-1 Long-Reach (80 km)	SFP-OC3-LR2
SFP OC-12/STM-4 Multimode	SFP-OC12-MM
SFP OC-12/STM-4 Short-Reach	SFP-OC12-SR
SFP OC-12/STM-4 Intermediate-Reach	SFP-OC12-IR1
SFP OC-12/STM-4 Long-Reach (40 km)	SFP-OC12-LR1
SFP OC-12/STM-4 Long-Reach (80 km)	SFP-OC12-LR2
SFP OC-48/STM-16 Short-Reach	SFP-OC48-SR
SFP OC-48/STM-16 Intermediate-Reach	SFP-OC48-IR1
SFP OC-48/STM-16 Long-Reach (80 km)	SFP-OC48-LR2

WARRANTY

- Standard warranty: 90 days.
- Extended warranty (optional): available under Cisco SMARTnet[®] support contract for the Cisco router chassis.

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StrataView Plus, TeleRouter, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R) 205309.BL_ETMG_CC_7.05