



VGA over Cat5 Receiver (ST121 Series)

StarTech ID: ST121R



The Converge A/V VGA over Cat5 video receiver works with the ST1214T. The video signal is sent to remote monitors over standard 4 pair Category 5 UTP cable using RJ45 connectors and supports distances of up to 150m / 500ft.

Allow Converge A/V to provide you with digital signage solutions. Applications include airports, bus depots, retail, or any large buildings where video needs to be delivered at long distances.

Applications and Solutions

- > For applications where the display is placed in a convenient viewing area, but the system equipment is placed elsewhere in a
- > Ideal for industrial sites with harsh environments
- > Ideal for digital signage applications in financial, educational, and business sectors
- > Ideal for video conferencing and demo stations

Features

- > Extends video cables by up to 500 ft. (150m)
- > Provides crystal clear picture quality
- > Pure hardware design, no software or drivers required
- > Supports VGA, SVGA, and Multisync monitors



The StarTech.com

Advantage:

Support and Resources: Single point of contact for all your questions; exclusive online tools and free live technical support

Save Time Sourcing: A complete selection of high-demand and hard-to-find products from one vendor

Best Value: StarTech.com products offer the best combination of features and price

Exclusive Resources: Complete product information and tools available at www.startech.com

- > Uses standard Category 5 straight-wired, twisted-pair, network patch cable for economical and reliable data transmission

Specifications

- > Color Black
- > Enclosure Type Aluminum
- > Maximum Cable Length 499.87 ft [152.4 m]
- > Number of Ports 1
- > Power Adapter Included Yes
- > Power Adapter - Amperage 600mA
- > Power Adapter - DC Voltage 9V DC
- > Center Tip Polarity Positive
- > Carton Quantity 12
- > Remote Unit Connectors 2 - DB15 High Density Female
- > Remote Unit Connectors 1 - RJ45 Female
- > Shipping (Package) Weight 1.33 lb [0.6 kg]
- > Cable Type Category 5 unshielded twisted pair (UTP)
- > Maximum Resolution 1024 x 768 @ 500 feet (150m)